



CHINA SOLAR


CHINA SOLAR

CHINA SOLAR LTD


solars-china.com
KaXiDy

CHINA SOLAR

CHINA SOLAR

15W CIRCULAR SOLAR PANEL

FRONT VIEW



SIDE VIEW

BACK VIEW

ELECTRICAL CHARACTERISTICS

Power	15W
Operating Voltage	18V
Operating Current	833mA
Type of solar cell	Monocrystalline Silicon Solar Cell
Power Tolerance	±5%
STC: Irradiance 1000W/m ² , Module temperature: 25°C, AM=1.5	

TEMPERATURE COEFFICIENTS

Nominal Operating Cell Temperature (NOCT): 45°C±2°C	
Temp. Coefficient of I _{sc}	(0.045±0.01)%/°C
Temp. Coefficient of V _{oc}	-(0.34±0.01)/°C
Temp. Coefficient of Power	-(0.47±0.05)%/°C

TESTED OPERATING CONDITIONS

Max load	50psf 245kg/m ² (2400)pascals
Hailstone impact	25mm(1inch) at 23m/s(52mph)
Temperature	-40° C to + 85° C

MECHANICAL SPECIFICATIONS

Dimensions	Ø475mm, Thickness: 4.5mm
Encapsulation	Glass/EVA/Cells/EVA/TPT
Front Glass	Tempered Glass, thickness: 3.2mm
Frame	Without frame, Solder wire, 450mm long
Efficiency	≥16%
Dimension Tolerance ±0.2mm	

FIGURE OF STRUCTURE**WARRANTIES**

Power output more than 90% for 10years
Power output more than 80% for 20years

THE TECHNICAL FILES PROVIDED BY CHINA SOLAR LTD

Office Address:
N0.601, ZhongKang Pioneer Park, ZhongKang Road,
Futian District, ShenZhen City, Guangdong Province, China
Factory Address:
Longxi Hi-tech Industrial Park, Longcheng Road, Longgang
Town, ShenZhen City, Guangdong Province, China

**CHINA SOLAR LTD**<http://www.solars-china.com><http://www.solars-china.net>

Tel: +86.755.8351 5659

Fax: +86.755.8271 6024

E-mail: market@solars-china.com